

---

*Transformer Darwin (#001)*

*Jean Chagas Vaz*

***Annotated bibliography***

*Dawin-OP (Spring/Summer 2017)*

**Paper one:** Humanoid navigation with dynamic footstep plans

**Web-link:** <http://ieeexplore.ieee.org/abstract/document/5979656/>

**Citation:** Garimort, J., Hornung, A. and Bennewitz, M., 2011, May. Humanoid navigation with dynamic footstep plans. In *Robotics and Automation (ICRA), 2011 IEEE International Conference on* (pp. 3982-3987). IEEE. This paper has been cited 41 times

### **Reader Description:**

Time to read/comment/highlight the full paper: *3 hours and 35 minutes*

This paper ***describes a navigation method called Lite D\* applied to Aldebaran NAO***. The big picture that motivates this paper is ***to develop an optimal footstep planning with an efficient collision detection and obstacle avoidance***. The critical gap the paper tries to fill is/are ***account for motion drift and determine the robot's pose in a 3D world model***. The approach used is: ***to use the manufacture's walking engine (Inverted Pendulum model) "footstep model"; Elaborate an incremental heuristic search algorithm(an extension of A\* method); change the starting states of the D\* lite code for a faster re-planner; Using a 2D grip map (Despite the fact that they mentioned 3D at the beginning of the paper)***. This approach's background stems from: ***local planner suggested by Okada[10]; global 2D path suggested buy Elmogy [11][12]; footstep basis using A\* argued by Chestnutt[13]; ZMP-based pattern generator suggested by Kanehiro [15]; probabilistic planner [16]***. The paper presents ***heuristic functions models(D\* Lite) (equations very unclear to follow, because my lack of knowledge), computer simulations (software not disclosed), experiments with NAO and a full sized humanoid (Honda's ASISMO; PS: allows step over obstacles)***. The selection ***of (D\* Lite) is because such method has been extensively used for robotics navigation stems based on the DARPA Grand Challenge [17]***. The results suggest that ***the humanoid can correct small deviations from the original footstep, therefore quickly re-planning its steps to avoid obstacles***. The paper concludes with ***an efficient way to plan motions for humanoid robots while***

*scanning the environment and responding to any barrier that it might encounter.*

The authors *mentioned to extend their planning method to a 3D environments for the future studies.*

Time to complete the description above: *1 hour and 23 minutes*

Reader's commentaries:

The paper is very well written, but the math and the equations are very hard to understand. The paper flows nicely with a clear progressive thoughts (INTRO->RELATED\_WORK->METHOD\_CHOSEN-.RESULTS->CONCLU). I did not understand this paper from "top to bottom", however I have gathered the main idea of it.

**PS: The full reviewed paper is attached at APENDIX-A. Due to copyrights policy such appendix ought to be used exclusively by the reader and the reader's advisor.**

**Paper Two:** Integrated Perception, Mapping, and Footstep Planning for Humanoid Navigation Among 3D Obstacles

**Web-link:** <http://ieeexplore.ieee.org/abstract/document/6696731/>

**Citation:** Maier, Daniel, Christian Lutz, and Maren Bennewitz. "Integrated perception, mapping, and footstep planning for humanoid navigation among 3D obstacles." *Intelligent Robots and Systems (IROS), 2013 IEEE/RSJ International Conference on*. IEEE, 2013. This paper has been cited 23 times

Time to read/comment/highlight the full paper: 5 hours and 19 minutes

This paper ***describes a real-time footstep planning method for applied to Aldebaran NAO***. The big picture that motivates this paper ***is to propose a combination of several methods and hardware that alongside with simulations and experimentation***. The critical gap the paper tries to fill is/are ***account for a method which allows humanoid robots to autonomously navigate into unknown environments***. The approach used is: ***to apply several techniques to accomplish an integrated navigation framework based on a combination of: pose estimation, mapping, and motion planning for autonomous navigation in unknown 3D environments.; use Aldebaran NAO for modifiable walking patterns***. This approach's background stems from: ***footstep planning (plus 3D obstacles) suggested by Perrin [7]; camera images to plan footsteps by Cupec [12] track objects in monocular images suggested by Michel [13]; 3D occupancy grid based argued by Gutmann [14]; a laser scanner mounted on a humanoid robot for environment mapping studied by Niwshiewaki***. The paper presents ***a combination of odometry with depth measurements, forward kinematics, and onboard IMU(inertia measurement unit) for "pose estimation"; a high-resolution heightmap for environment representation; inverse heightmap (IHM) for collision check; ARA\* method for footstep planning, experiments with NAO***.

The selection *of the methods mentioned above were chosen due their unique capability of effectively and autonomously walk into cluttered environments. The results suggest that.* The paper concludes *that the **first** system that combines these techniques in a unique framework.*

. The authors *did not mentioned future studies.*

Time to complete the description above: *1 hour and 34 minutes*

Reader's commentaries:

The paper has a tremendous structure( I will use it as template). It also combines a lot of advance computer science, most of the information on this paper is brand new to me. I have no clue how the authors are able to get those types of simulation.

**PS: The full reviewed paper is attached at APENDIX-A. Due to copyrights policy such appendix ought to be used exclusively by the reader and the reader's advisor.**

**Paper Three:** Real-time Footstep Planning and Following for Navigation of Humanoid Robots

**Web-link:**

<http://www.jeet.or.kr/LTKPSWeb/uploadfiles/be/201507/270720151457568285000.pdf>

**Citation:** Hong, Young-Dae. "Real-time footstep planning and following for navigation of humanoid robots." J. Elect. Eng. Technol 10.5 (2015): 2142-2148. This paper has been cited 5 times

**Reader Description:**

Time to read/comment/highlight the full paper: *4 hours and 08 minutes*

This paper integrates a navigation system ***describes a real-time footstep planning method for applied to DARwIn-OP***. The big picture that motivates this paper ***is to propose a method that is effective and verified by experimentation and simulation***. The critical gap the paper tries to fill is/are ***account for a novel real-time real-time footstep planning and following methods for the navigation***. The approach used is: ***to apply the so-called "evolutionary optimization algorithm" to plan the optimal footstep sequences; use DARwIn-OP walking engine (Inverted Pendulum model) for modifiable walking patterns; use the uni-vector field method for walking direction***. This approach's background stems from: ***uni-vector field method suggested by Kim [10]; walking pattern generator based on the 3-D LIPM suggested by Lee [12]***. The paper presents ***uni-vector field navigation method is utilized for walking direction, computer simulations (Webots, very little information on how was done though), experiments with DARwIn-OP***. The selection ***of the uni-vector field method is because it allows real-time owing to using low computing power*** based on the previous work presented by Kim [10]. The results suggest that ***"the humanoid robot successfully arrived at the goal without obstacle collisions following the planned***

***footsteps in real-time”[Hong]. The paper concludes that the proposed method yielded satisfactory results based on experiments and simulations.***

. The authors ***did not mentioned future studies.***

Time to complete the description above: *55 minutes*

Reader’s commentaries:

The paper is not helpful in terms of “explaining the physics and mathematics” behind the method proposed. I am sure that I cannot reproduce what the author has done, however I also cannot argues with the overall logic of the paper. There is almost nonexistent mention regarding the simulation.

**PS: The full reviewed paper is attached at APENDIX-A. Due to copyrights policy such appendix ought to be used exclusively by the reader and the reader’s advisor.**